

For a more colourful world, we all need to be a little greener

Jotun's greatest contribution to the environment and society is our premium coating systems protecting property against decay and corrosion.

Jotun has contributed to the environment for decades by offering high quality products and solutions. We also use a lot of resources in developing product ranges for our customers that exceed the legal requirements, because we want to be ahead.

We know that our customers like to contribute to the environment and therefore we are able to offer products and solutions that really make a difference. At the same time, we never make compromises on high quality and durability.


As we take continuous steps to better protect your property, we're also taking even greater steps to better protect our environment. We call it Jotun GreenSteps – steps that make a significant difference to the world we all share:



Solvalitt

Heat Resistant Coatings Colour Card






White
(Close to RAL 9016) ●



Black
(Close to RAL 9004) ●




Aluminium
(Close to RAL 9006)




Yellow




Orange
(Close to RAL 2010) ●




Light grey
(Close to RAL 7047) ●




Grey
(Close to RAL 7040) ●




Reddish orange
(Close to RAL 2002) ●



Bright red
(Close to RAL 3000) ●



Red
(Close to RAL 3009)



Green
(Close to RAL 6010)

In addition to the colour samples shown Solvalitt and Solvalitt Midtherm can also be offered in heat resistant shades close to:

RAL 1021 (Solvalitt Midtherm only)

RAL 7010

RAL 7038

RAL 8001

The reference colours have to be considered as visual equivalents.

● Slight colour change at 200°C

● Solvalitt: Colour change at 450°C

Solvalitt

Solvalitt | MIDTHERM

Solvalitt and Solvalitt Midtherm are Jotun's one component physically drying silicon acrylic heat resistant coatings.

These two products are designed to be heat resistant finish coats and as such they are provided in a range of colours.

Solvalitt Midtherm is heat resistant up to 260°C.

Solvalitt is heat resistant up to 600°C.

Due to variations in the thermal stability of pigments, slight colour changes can occur when the coating is heated. These changes have been indicated next to the colour chips for each product. Note that such a colour change will not affect the performance of the coating.

Deviations between the samples shown, the delivered products and the standard references may occur due to differences in production methods, pigments and gloss levels.

Additional colours may be provided, however, due to the limited thermal stability of organic colour, changes in the products when exposed to heat must be expected.

Commonly used colours for pipes:

Yellow	Flammable fluids & gases
Red	Fire-quenching fluids
Orange	Toxic or corrosive fluids & gases
Green	All water (potable, boiler etc.)
Brown	Combustible fluids & gases