

YachtCare Cleaner

Product description

This is a pH neutral foaming detergent. Special polymers provide self-drying icing effect. It is biological degradable.

Typical use

Can be used on painted surfaces, glass, gelcoat, fiberglass, carbon, plexiglass etc.
For manual washing of exterior surfaces of yachts. After rinsing it occurs an uniform and gradual withdrawal of water which prevents the formation of drops and calcareous/saline residue, leaving the surface clean and shiny. To prepare the solution, dose 20-30 ml for every 1L of water.

Approvals and certificates

Complies with the criteria in MARPOL 73/78 Annex 5 part 1.7.5 and is therefore not harmful to the marine environment.

Additional certificates and approvals may be available on request.

Colours

translucent green

Product data

Property	Test/Standard	Description
Flash point	ISO 3679 Method 1	non-flammable
Density	calculated	1 kg/l
VOC-EU	IED (2010/75/EU) (theoretical)	0 g/l

The provided data is typical for factory produced products, subject to slight variation depending on colour.

Application

Application methods

The product can be applied by

Brush: Recommended

Cotton, Rag, Sponge, 3M pad: May be used.

Product mixing

Single pack

Thinner/Cleaning solvent

Thinner: Water

Cleaning of painting tools: Water

Product compatibility

Previous coat: alkyd, acrylic, epoxy, polyurethane

Packaging (typical)

	Volume (litres)	Size of containers (litres)
YachtCare Cleaner	1 / 5	1 / 5

The volume stated is for factory made colours. Note that local variants in pack size and filled volumes can vary due to local regulations.

Storage

The product must be stored in accordance with national regulations. Keep the containers in a dry, cool, well ventilated space and away from sources of heat and ignition. Containers must be kept tightly closed. Handle with care.

Shelf life at 23 °C

YachtCare Cleaner 48 month(s)

In some markets commercial shelf life can be dictated shorter by local legislation. The above is minimum shelf life, thereafter the paint quality is subject to re-inspection.

Disposal of waste

N/A

Caution

The product is suitable for both professional and consumer application. The applicators and operators shall be trained, experienced and have the capability and equipment to mix/stir and apply the coatings correctly and according to Jotun's technical documentation. Applicators and operators shall use appropriate personal protection equipment when using this product. This guideline is given based on the current knowledge of the product.

Health and safety

Please observe the precautionary notices displayed on the container. Use under well ventilated conditions. Do not inhale spray mist. Avoid skin contact. Spillage on the skin should immediately be removed with suitable cleanser, soap and water. Eyes should be well flushed with water and medical attention sought immediately.

Colour variation

When applicable, products primarily meant for use as primers or antifoulings may have slight colour variations from batch to batch. Such products and epoxy based products used as a finish coat may chalk when exposed to sunlight and weathering.

Colour and gloss retention on topcoats/finish coats may vary depending on type of colour, exposure environment such as temperature, UV intensity etc., application quality and generic type of paint. Contact your local Jotun office for further information.

Disclaimer

The information in this document is given to the best of Jotun's knowledge, based on laboratory testing and practical experience. Jotun's products are considered as semi-finished goods and as such, products are often used under conditions beyond Jotun's control. Jotun cannot guarantee anything but the quality of the product itself. Minor product variations may be implemented in order to comply with local requirements. Jotun reserves the right to change the given data without further notice.

Users should always consult Jotun for specific guidance on the general suitability of this product for their needs and specific application practices.

If there is any inconsistency between different language issues of this document, the English (United Kingdom) version will prevail.
