

## Jotun Thinner No. 7

### Product description

#### Type

This is a paint thinner. Designed to improve the flow of a range of Jotun acrylic, vinyl and antifouling coatings. Can also be used as cleaner for pumps and tools before and after painting.

#### Recommended use

Recommended usage as per technical datasheet or application guide for the specific product to be applied.

### Product data

#### Packaging (typical):

<b>Colors</b>	Clear	
<b>Generic type:</b>	Thinner	
<b>Solids by volume:</b>	0 ± 2 volume%	
<b>Density:</b>	0.87 g/cm <sup>3</sup>	calculated
<b>Flash point:</b>	25 °C	
<b>VOC-EU:</b>	870 g/l	IED (2010/75/EU) (theoretical)
<b>VOC:</b>	871 g/l	US EPA method 24
<b>VOC-Solvent Emission Directive:</b>	1000 g/kg	SED (1999/13/EC)

### Application data

Film thickness per coat (µm)	
Wet (calculated)	Dry (calculated)

### Directions for use

#### Shelf life at 23 °C

Thinner No. 7 48 month(s)

In some markets commercial shelf life can be dictated shorter by local legislation. The above is minimum shelf life, thereafter the paint quality is subject to re-inspection.

## Disposal of waste

## Health and safety

Please observe the environmental and precautionary notices displayed on the container.

A Material Safety Data Sheet for the product has been issued.

Detailed information regarding health and safety risks and precautions for the use of this product is specified in the product's Safety Data Sheet.

**First-aid measures**, refer to section 4.

**Handling and storage**, refer to section 7.

**Transport information**, refer to section 14.

**Regulatory information**, refer to section 15.

Please observe the precautionary notices displayed on the container. Use under well ventilated conditions. Do not inhale spray mist. Avoid skin contact. Spillage on the skin should immediately be removed with suitable cleanser, soap and water. Eyes should be well flushed with water and medical attention sought immediately.

## Color variation

When applicable, products primarily meant for use as primers or antifoulings may have slight color variations from batch to batch. Such products may fade and chalk when exposed to sunlight and weathering.

Color and gloss retention on topcoats/finish coats may vary depending on type of color, exposure environment such as temperature, UV intensity etc., and application quality. Contact your local Jotun office for further information.

## Miscellaneous

### NOBB number

This document covers the following NOBB numbers:

50067545

### NOBB module number

42018583

### Contact information

Jotun A/S  
P.O.Box 2021  
3202 Sandefjord  
Tel: 33 45 70 00

### Disclaimer

The information in this document is given to the best of Jotun's knowledge, based on laboratory testing and practical experience. Jotun's products are considered as semi-finished goods and as such, products are often used under conditions beyond Jotun's control. Jotun cannot guarantee anything but the quality of the product itself. Minor product variations may be implemented in order to comply with local requirements. Jotun reserves the right to change the given data without further notice.

Users should always consult Jotun for specific guidance on the general suitability of this product for their needs and specific application practices.

If there is any inconsistency between different language issues of this document, the English (Eng) version will prevail.

**Technical Data Sheet**  
**Jotun Thinner No. 7**

